
Product Information

A PRODUCT OF VALVOLINE, A DIVISION OF ASHLAND INC. USA



VALVOLINE ALL FLEET TURBO 20W50

Valvoline All Fleet Turbo 20W50 is formulated to provide optimum performance in modern naturally aspirated and turbo charged diesel engines operating under a wide variety of service conditions. It is blended with premium base stocks and high quality additive chemistry.

Valvoline All Fleet Turbo 20W50 is recommended for all equipment such as trucks, buses, excavators, tippers & dozers fitted with turbo charged diesel engines.

Also suitable for other vehicles such as LCV's / MUV's of all makes.

VALVOLINE ALL FLEET TURBO 20W50 ADVANTAGE

- High temperature piston deposit control
- Soot dispersancy and oil-thickening control
- Low temperature sludge protection
- Superior TBN retention to neutralize corrosive acids from combustion.
- Foam protection
- Oxidation inhibition
- Corrosion and rust inhibition
- Valve train wear protection

Performance levels / Approvals

API CF-4/SG

Typical Characteristics

| | |
|----------------------------------|----------------|
| Appearance | Bright & Clear |
| Kinematic Viscosity, cSt @ 40°C | 155.40 |
| Kinematic Viscosity, cSt @ 100°C | 17.10 |
| Viscosity Index | 118 |
| TBN, mg KOH/g | 7.2 |
| Flash Point, COC, °C | 210 |
| Pour Point, oC, Max. | -24 |
| CCS Viscosity @ -15 °C, cP, Max. | 9200 |

Available configurations: 24 x 1L Case, 4 x 5L Case, 1 x 18L, 1 x 200L

This information only applies to products manufactured in the following location(s) – Singapore

Effective date
28th April 2009

Authors Initials
SKM

Product code